

STANDARD

BETEX SUPER 24 kVA

AREAS OF APPLICATION:

- Chemical industry
- Steel industry
- Paper industry
- Gearbox manufacturers
- Machine building
- Transport sector
- MRO/OEM sector
- Wind energy
- Power plants
- Mining industry



Heavy duty heaters.

- Min. ID Ø: 60 mm
- Max. OD Ø: 900/1300 mm
- Max. width: 400/700 mm
- Automatic demagnetisation
- Automatic power reduction
- Yokes: selection of 5 sizes

- Max. bearing weight: 600 kg
- Max. weight other parts: 350 kg

Optional:

- electric crane
- enlarged width 700 mm: DL700

NB: these technical data are indicative and dependent on the amount of power and type of heater.

Technical details page 32



Heating times are subject to the relationship between:

- Min. bore and max. outside diameter, width, weight.
- Required temperature and material type.
- Available power.



TURBO

BETEX SUPER TURBO 24 kVA

AREAS OF APPLICATION:

- Chemical industry
- Steel industry
- Paper industry
- Gearbox manufacturers
- Machine building
- Transport sector
- MRO/OEM sector
- Wind energy
- Power plants
- Mining industry



✓ High output,
energy efficient!



Heavy duty heaters.

- Min. ID Ø: 145/195 mm
- Max. OD Ø: 1700 mm
- Max. width: 600 mm
- Automatic demagnetisation
- Automatic power reduction
- Including 1 yoke

- Max. bearing weight: 1200 kg
- Max. weight other parts: 900 kg

NB: these technical data are indicative and dependent on the amount of power and type of heater.

Technical details page 32

The TURBO effect only works when the component is in a horizontal position

